

TANNERS CHOICE PROTECTOR

Leather Protector and Restorer


Product

- ✓ Ensures leather does not dry out or crack prematurely
- ✓ Forms a film that penetrates and bonds to the surface, creating a tough barrier layer that helps resist spillages, abrasives and grime
- ✓ Contains no silicone-based products that offer poor protection against hot or oil-based spills
- ✓ Once protected leather sheds dust making it easier to clean

Leather cleaner and protection that is simple and safe on all leathers. When applied to freshly cleaned or new leather it dries to a natural soft sheen and will only show higher sheen when more than two coats are applied.



Technical

Colour	White	Product Code	Description	Outer Pack	APN
Odour	Ketone	165190	CHRC-20606 Tanners Protect 1L	6	9324828002451
pH	N/A				
Dangerous Goods Classification					
ADG CODE	1263, PAINT				
HAZCHEM	•3Y				
CLASS	3: Flammable liquids				
PACK GRP	III				

Application

Method

1. Do not dilute. Use neat. Apply using a clean, damp and lint free cloth.
2. Pour a small quantity of PROTECTOR onto a pad and apply to back of the article first in firm even strokes, slightly rubbing into edges and crevices. Never rub freshly applied coats as this will permanently smear or streak the partly dried surface.
3. If the coat is uneven, buff out with dry towelling after the surface is tack free after about 10 mins.
4. A second coat can be applied across the direction of the previous coat to increase protection on seat, cushions and arm rests. (This may be required on seat cushions and arm rests where heavy wear protection is required).
5. Allow approximately 30 – 45 minutes to dry between coats.
6. Repeat process section by section until item has been coated.
7. After surface has been protected it will be safe to use once the solvent smell has dissipated (usually a few hours after treatment).

Continued next page

Version: 4 Page 1 of 2

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au. This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.

TANNERS CHOICE PROTECTOR

Leather Protector and Restorer

Application precautions:

- ✓ DO NOT apply in direct sun light or areas of strong wind, as high-speed drying increases the chance for streaking and poor levelling.
- ✓ Dampen clean non-linting flannel or pure cotton cloth (not towelling) if weather is hot. DO NOT add water to Protector as this will promote streaking. Once you are experienced, a dry flannel may be used.
- ✓ Wring out all excess water and double over to make a pad.
- ✓ This system is NOT suitable for or on Nubuck or suede surfaces.

Hazard Statement

- H226: Flammable liquid and vapour.
- H315: Causes skin irritation.
- H320: Causes eye irritation.
- H335: May cause respiratory irritation.
- AUH066: Repeated exposure may cause skin dryness or cracking.

Prevention

- P102: Keep out of reach of children.
- P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
- P243: Take precautionary measures against static discharge.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P264: Wash contacted areas thoroughly after handling.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves, protective clothing and eye or face protection.